

1/4 - 14 x 0.88" HWH DP1 6" O/C

"SRC-02" METAL CLOSURE, REFER TO SHEET __ FOR FASTENING INFORMATION

SR2 OUTSIDE CLOSURE STRIP SET IN 1" x 3/16" BUTYL TAPE AT TOP AND BOTTOM

BUTYL TAPE SEALANT

FIELD-FILL W/ COMPRESSIBLE INSULATION (NOT BY IMP SUPPLIER)

"HE_S" HIGH EAVE TRIM

"WC-01" PANEL CLIP W/ () 1/4 - 14 x _ HWH DP3 W/O WASHER AT PANEL JOINT

POP RIVET 12" O/C

BUTYL SEALANT AT VERTICAL JOINT

1/2"

1" x 3/16" BUTYL TAPE SEALANT AT TOP AND BOTTOM

NOTE: BARE SRC- PROVIDED FOR PROJECTS WITH ROOF SLOPE ≤ 1:12 AND EAVE HEIGHT ≥ 20'.

SR_ ROOF PANEL CLIP W/ () 1/4 - 14 x 2" HWH DP3 W/O WASHER, PER CLIP, PER PANEL AT HIGH EAVE STRUT


BUTYL TAPE SEALANT (MARRY TO VERTICAL SEALANT)

EAVE STRUT (NOT BY IMP SUPPLIER)

NOTE: DO NOT OVER-DRIVE FASTENERS. IF THE METAL AT THE EDGE OF THE PANEL IS DEFORMED OUT OF PLANE, THE ADJACENT PANEL WILL BE DIFFICULT TO ENGAGE AND WILL NOT SEAM. AFTER SR CLIP HAS BEEN INSTALLED OVER MALE LEG OF STANDING SEAM PANEL, PRE-CRIMP, USING 1/2" HAND CRIMPING TOOL.

HIGH EAVE

(SECTION VIEW)



DETAIL:

HIGH EAVE

929 ALDRIDGE ROAD
VACAVILLE, CA 95688
TEL: (707) 359-2280
FAX: (707) 359-2286
WWW.AWIPANELS.COM

All Weather
Insulated Panels



APPLICATION:
SR ROOF, COMMERCIAL & INDUSTRIAL
AWIP DETAIL NUMBER:
SRR-ACH-E-001

DATE:

08/23/24

SHEET:

DRAWN BY:

MMF

1

OF 1